

SUPER PEEWEE® III+ dolly by Chapman

SPECIFICATIONS

Carrying weight	280 lbs	127 kg
Operational weight	329 lbs	149 kg
*Maximum payload	250 lbs	113 kg
**Maximum payload with center mount kit	1,100 lbs	499 kg
Maximum camera mount height (position 1 -90° mode)	4ft 11 ¾ in	1.51 m
Maximum camera mount height (position 2 -45° mode)	4ft 9 1/2 in	1.46 m
Maximum camera mount height (position 3 -low mode)	4ft 2 1/2 in	1.28 m
Vertical boom travel (position 1 - 90° mode)	30 1/4 in	77 cm
Vertical boom travel (position 2 - 45° mode)	32 in	81 cm
Vertical boom travel (position 3 - low mode)	3 1/4 in	79 cm
Vertical boom travel (position 4 - extender mode)	38 1/4 in	97 cm
Maximum boom lifts (fully charged)	4 Lifts	
Chassis maximum length (wheels fully extended)	43 in	1.09 m
Chassis minimum length (wheels fully retracted)	34 1/2 in	88 cm
Minimum chassis height for transportation	16 in	41 cm
Chassis width - legs at 0° position	20 in	51 cm
Chassis width - legs at 90° position	32 in	81 cm
Steering low post height	35 in	89 cm
Steering high post height	38 in	97 cm
Accumulator charging time (empty to full)	60 sec	
Dolly Shipping Weight	475 lbs	215,4 kg
Dolly Shipping Dimensions	L 43 in x W 27 in x H 36 in	
Dolly Accessory Crate Weight	346 lbs	156.9 kg
Dolly Accessory Crate Dimensions	L 44 in x W 35 in x H 28 in	

*Payload includes all items (i.e. man, camera) on arm.